



molybdenum disulfide

Technical, Technical Fine, Super-Fine

MoS₂

- MIL-M-7866
- AMS-M-7866
- Small Sizes
- Fiber Drums
- Custom Formulations

Rose Mill Company, manufacturer of Bemol brand lubricants, offers technical grade, technical fine grade, and super-fine grade molybdenum disulfide powder for use in lubricant manufacturing and end-use applications. Technical grade is manufactured in accordance with MIL/AMS-M-7866.

Rose Mill stocks MoS₂ in 1 lb., 5 lb., and 25 lb. plastic pails (available online at www.RoseMill.com), and 200-250 lb. fiber drums. Custom packaging, custom formulations, and custom powdering is available to meet your specifications. Contact us for details.

Product Analysis

Molybdenum Disulfide (MoS₂) CAS 1317-33-5

Typical Analysis	Technical	Technical Fine	Super-Fine
MoS ₂	98.0% min.	98.0% min.	98.0% min.
Acid (insoluble)	0.50% max.	0.50% max.	0.50% max.
Fe	0.25% max.	0.25% max.	0.25% max.
MoO ₃	0.05% max.	0.05% max.	0.15% max.
H ₂ O	0.02% max.	0.05% max.	0.15% max.
Oil	0.05% max.	0.40% max.	0.40% max.
C	1.50% max.	1.50% max.	1.50% max.
Acid Number	0.05	0.25	3.0
Particle Size (avg.)	30 um	6 um	1.5 um
Malvern (in 2-propanol)	90% <78.38	90% <11.82	90% <4.38
	50% <31.59	50% <5.22	50% <2.05
	10% <9.44	10% <1.97	10% <1.00

GENERAL PROPERTIES

Hardness	1-1.5 Mohs scale (basal plane)
Density	4.96 +/-0.03 (x-ray diffraction calculation)
Wettability	60° contact angle ^w /water
Electrical	Semi-conductor <i>p</i> or <i>n</i> type

Rose Mill Co.
100 Brook Street
West Hartford, CT 06110
USA
www.RoseMill.com
info@RoseMill.com

(860)232-9990 phone
(860)232-9995 fax

