



tungsten disulfide

high-performance lubricant powder



- Small Sizes
- Fiber Drums
- Custom Formulations

Rose Mill Company, manufacturer of Bemol brand lubricants, offers 99.9% minimum purity tungsten disulfide powder. Our tungsten disulfide powder has a 0.03 coefficient of friction, withstands pressures up to 300,000 psi, and has a working temperature range of -450°F to 1200°F.

Rose Mill stocks WS₂ powder in 1/2 lb., 5 lb., and 25 lb. plastic pails (available online at www.RoseMill.com), and 50-100 lb. fiber drums. Custom packaging, custom formulation, and custom powdering is available to meet your specifications. Contact us for details.

Product Analysis

Tungsten Disulfide (WS₂)

CAS 12318-09-9

Typical Analysis	Maximum %
WS ₂	99.90 min.
W	74.14 avg.
S	25.65 avg.
H ₂ O	0.0500
Fe	0.0010
Al	0.0004
Si	0.0006
Cu	0.0005
Mg	0.0002
Ca	0.0010
Ni	0.0007
C	0.0013
Mo	0.0020
Other	0.0423
FSSS particle size	1.1 um

Rose Mill Co.
100 Brook Street
West Hartford, CT 06110
USA

www.RoseMill.com
info@RoseMill.com

(860)232-9990 phone
(860)232-9995 fax

